



CITY OF GREEN COVE SPRINGS  
321 WALNUT STREET  
GREEN COVE SPRINGS, FL 32043

**WATER BARRIER/SHEATHING RENAILING AFFIDAVIT**

PERMIT NUMBER \_\_\_\_\_

OWNER \_\_\_\_\_

JOB ADDRESS \_\_\_\_\_

I HERBY CERTIFY THAT:

**A. THE DECK HAS BEEN RE-NAILED AT 6" ON CENTER FOR PLYWOOD DECKS AND 2 FASTENERS PER BOARD FOR BOARD ON BOARD DECKS WITH 8D RING SHANK NAILS WITH THE FOLLOWING MINIMUM DIMENSIONS:**

- 1) 0.113-INCH NOMINAL SHANK DIAMETER
- 2) RING DIAMETER OF 0.012 OVER THE SHANK DIAMETER
- 3) 16 TO 20 SHANKS PER INCH
- 4) 0.280 INCH FULL ROUND HEAD DIAMETER
- 5) RING SHANK TO EXTEND A MINIMUM OF 1 1/2" FROM THE TIP OF THE NAIL
- 6) 2 1/2 INCH NAIL LENGTH.

**B. A SECONDARY WATER BARRIER HAS BEEN HAS BEEN INSTALLED AS FOLLOWS:**

\_\_\_\_\_ 4" STRIP OF SELF-ADHERING POLYMER MODIFIED BITUMEN TAPE HAS BEEN APPLIED TO ALL JOINTS IN THE PLYWOOD DECK.

\_\_\_\_\_ AN ASPHALT IMPREGNATED 30# FELT UNDERLAYMENT HAS BEEN INSTALLED PER FBC HVHZ.

**EXCEPTIONS**

- 1) ROOF SLOPES < 2:12 HAVING A CONTINUOUS ROOF SYSTEM SHALL BE DEEMED TO COMPLY WITH REQUIREMENTS FOR A SECONDARY WATER BARRIER.
- 2) CLAY AND CONCRETE TILE ROOF SYSTEMS INSTALLED AS REQUIRED BY THE FLORIDA BUILDING CODE ARE DEEMED TO COMPLY WITH THE REQUIREMENTS FOR SECONDARY WATER BARRIERS.

**C. A COPY OF THIS AFFIDAVIT HAS BEEN DELIVERED TO THE HOMEOWNER.**

Roofing Qualifier's Signature: \_\_\_\_\_ Date: \_\_\_\_\_

Before me this \_\_\_\_\_ day of \_\_\_\_\_ 20\_\_\_\_  
in the County of Clay, State of Florida, has personally appeared

\_\_\_\_\_ herein by himself/herself  
and affirms all statements and declarations herein are true and accurate.

\_\_\_\_\_  
Notary Public at Large

State of Florida, County of Clay

Personally Known or Produced Identification ID Type \_\_\_\_\_